

# StimConnect<sup>®</sup>

## Disposable connection cables for PACE<sup>®</sup> Model 300 (P/N 2005)

StimConnect<sup>®</sup> connection cables are available in color and length as indicated.



PACE<sup>®</sup> Model 300 with collets (clamping terminals) accepting pins of 0.9 to 2.0 mm

(order number: P/N 2005)

Connection pacemaker	Disposable connection cable StimConnect <sup>®</sup>		Connection pacing electrode/ lead
	Connection to pacemaker	Connection to pacing electrode	
	<p>Osyпка plug with 2 mm pins, touch protected</p>  <p>Length: 2.0 m SC.B/TSP/OSY (blue)</p>	<p>Terminal for shrouded 2 mm pins</p>  <p>Order number: SC.W/TSP/OSY (white)</p>	<p>Example: Plugs with unipolar shrouded pin</p> 
	<p>Osyпка plug with 2 mm pins, touch protected</p>  <p>Length: 2.0 m SC.B/TBOX/OSY (blue)</p>	<p>Terminal with sided clamping screws for exposed 0.1 to 2.0 mm pins</p>  <p>Order number: SC.W/TBOX/OSY (white)</p>	<p>Example: Plugs with unipolar exposed pin</p> 
	<p>Osyпка plug with 2 mm pins, touch protected</p>  <p>Length: 2.5 m SC.B/TCO/OSY (blue)</p>	<p>Terminal for exposed 0.9 to 2.0 mm pins</p>  <p>Order number: SC.W/TCO/OSY (white)</p>	<p>Example: Plugs with unipolar exposed pin</p> 
	<p>Plugs with unipolar exposed 2 mm pin, with protection cap</p>  <p>Length: 2.0 m SC.B/TSP/OP (blue)</p>	<p>Terminal for shrouded 2 mm pins</p>  <p>Order number: SC.W/TSP/OP (white)</p>	<p>Example: Plugs with unipolar shrouded pin</p> 
	<p>Plugs with unipolar exposed 2 mm pin, with protection cap</p>  <p>Length: 2.0 m SC.B/TBOX/OP (blue)</p>	<p>Terminal with sided clamping screws for exposed 0.1 to 2.0 mm pins</p>  <p>Order number: SC.W/TBOX/OP (white)</p>	<p>Example: Plugs with unipolar exposed pin</p> 
	<p>Plugs with unipolar exposed 2 mm pin, with protection cap</p>  <p>Length: 2.5 m SC.W/TCO/OP (white)</p>	<p>Terminal for exposed 0.9 to 2.0 mm pins</p>  <p>Order number: SC.W/TCO/OP (white)</p>	<p>Example: Plugs with unipolar exposed pin</p> 

# StimConnect®

## Reusable connection cables for PACE® Model 300 (P/N 2005)



StimConnect® connection cables are available in color and length as indicated



PACE® Model 300 with collets (clamping terminals) accepting pins of 0.9 to 2.0 mm

(order number: P/N 2005)

SCPACE300EN220406

Connection pacemaker	Reusable connection cable StimConnect®		Connection pacing electrode/ lead
	Connection to pacemaker	Connection to pacing electrode	
	<p>Plugs unipolar exposed 2 mm pin, with protection cap</p>  <p>Length: 2.0 m Order number: SC.RB/TBOX/SP (blue)</p>	<p>Terminal with sided clamping screws for exposed 0.1 to 2.0 mm pins</p>  <p>Order number: SC.RW/TBOX/SP (white)</p>	<p>Example: Plugs with unipolar exposed pin</p> 