







StimConnect™

for PACE® Model 101 with Unipolar Terminals

Extension Cables for Transvenous Pacing Applications

PACE® Model 101 is primarily used for temporary transvenous cardiac pacing applications. Transvenous leads for temporary pacing are either equipped with 2 mm shrouded plug pins or exposed (naked) plug pins. Following StimConnect® extension cables are recommended for PACE® Model 101 with unipolar terminals.

Pacemaker	Disposable Extension Cable StimConnect™		Transvenous Pacing Lead
	Connection Pacemaker- Side	Connection Patient-Side	
 <p>PACE 101 OSYPKA MEDICAL</p> <p>PACE® Model 101 with unipolar terminals accepting pins of 0.9 to 2.0 mm (order number: P/N 2001).</p> 	 <p>Article No: 82207BL</p> <p>Touch protected plug fitting unipolar terminals of PACE® Model 101</p> <p>Connects shrouded pins of transvenous leads</p> <p>Packaging Unit: 10 Pieces</p>	 <p>Shrouded pins (ø 2 mm)</p>	
	 <p>Article No: 81987BL</p> <p>Touch protected plug fitting unipolar terminals of PACE® Model 101</p> <p>Connects exposed (naked) pins of transvenous leads</p> <p>Packaging Unit: 5 Pieces</p>	 <p>Exposed (naked) pins (ø 2 mm)</p>	



Products and options may not be available or may vary by region and country. Please contact mail@osypkamed.com for availability in your region and country, for more information and for other StimConnect® extension cable variants.

StimConnect™

for PACE® Model 101 with Bipolar Terminal

Extension Cables for Transvenous Pacing Applications

PACE® Model 101 is primarily used for temporary transvenous cardiac pacing applications. Transvenous leads for temporary pacing are either equipped with 2 mm shrouded plug pins or exposed (naked) plug pins. Following StimConnect® extension cables are recommended for PACE® Model 101 with bipolar terminals.

Pacemaker	Disposable Extension Cable StimConnect™		Transvenous Pacing Lead
	Connection Pacemaker- Side	Connection Patient-Side	
 <p>PACE® Model 101 with bipolar terminal (order number: P/N 2004)</p>	 <p>Article No: 82208BL</p> <p>Bipolar plug fitting bipolar terminal of PACE® Model 101</p> <p>Packaging Unit: 10 Pieces</p>	 <p>Article No: 82203BL</p> <p>Bipolar plug fitting bipolar terminal of PACE® Model 101</p> <p>Packaging Unit: 10 Pieces</p>	 <p>Shrouded pins (ø 2 mm)</p>
	 <p>Exposed (naked) pins (ø 2 mm)</p>		



Products and options may not be available or may vary by region and country. Please contact mail@osypkamed.com for availability in your region and country, for more information and for other StimConnect® extension cable variants.







StimConnect™

for PACE® Model 203 with Unipolar Terminals

Extension Cables for Surgical Pacing Applications

PACE® Model 203 is primarily used for temporary surgical cardiac pacing applications. Surgical wires (temporary myocardial electrodes or heart wires) for temporary pacing are either equipped with 2 mm exposed (naked) plug pins or 0.9 mm pins/ needles. Following StimConnect® extension cables are recommended for PACE® Model 203 with unipolar terminals.

Disposable cables are for single use, reusable extension cables can be sterilized 25 times by ethylene oxide or steam. A punch card allows the identification of the sterilization cycles.

Pacemaker	Disposable Extension Cable StimConnect™		Surgical Pacing Electrode
	Connection Pacemaker- Side	Connection Patient-Side	
 <p>PACE® Model 203 with unipolar terminals accepting pins of 0.9 to 2.0 mm</p> <p>(order number: P/N 2002)</p>	 <p>Article No: 81987BL (blue) / 81987 WS (white)</p> <p>Plugs with touch protected 2 mm pins fitting unipolar terminals of PACE® Model 203</p> <p>Connects exposed (naked) pins with diameter between 0.9 to 2.0 mm</p> <p>Packaging Unit: 5 Pieces</p>		 <p>Adapters with exposed (naked) 2 mm pins</p> <p>Exposed (naked) 0.9 mm pins/ breaking needles</p>
	 <p>Article No: 81830</p> <p>Plugs with exposed 2 mm pins fitting unipolar terminals of PACE® Model 203</p> <p>Covered alligator clips allow versatile connection</p> <p>Packaging Unit: 10 Pieces</p>		
	 <p>Article No: 81828BL (blue) / 81828 WS (white)</p> <p>Plugs with exposed 2 mm pins fitting unipolar terminals of PACE® Model 203</p> <p>Connects exposed (naked) pins with diameter between 0 to 2.0 mm</p> <p>Packaging Unit: 5 Pieces</p>		 <p>Adapters with exposed (naked) 2 mm pins</p> <p>Exposed (naked) 0.9 mm pins/ breaking needles</p>



Products and options may not be available or may vary by region and country. Please contact mail@osypkamed.com for availability in your region and country, for more information and for other StimConnect® extension cable variants.

StimConnect™ for PACE® Model 203 with Unipolar Terminals

Extension Cables for Surgical Pacing Applications

PACE® Model 203 is primarily used for temporary surgical cardiac pacing applications. Surgical wires (temporary myocardial electrodes or heart wires) for temporary pacing are either equipped with 2 mm exposed (naked) plug pins or 0.9 mm pins/ needles. Following StimConnect® extension cables are recommended for PACE® Model 203 with bipolar terminals.

Disposable cables are for single use, reusable extension cables can be sterilized 25 times by ethylene oxide or steam. A punch card allows the identification of the sterilization cycles.

Pacemaker	Disposable Extension Cable StimConnect™		Surgical Pacing Electrode
	Connection Pacemaker- Side	Connection Patient-Side	
 <p>PACE® Model 203 with bipolar terminals (order number: P/N 2003)</p>	 <p>Article No: 82203BL (blue) / 82203WS (white)</p> <p>Bipolar plug fitting bipolar terminals of PACE® Model 203</p> <p>Connects exposed (naked) pins with diameter between 0.9 to 2.0 mm</p> <p>Packaging Unit: 10 Pieces</p>		 <p>Adapters with exposed (naked) 2 mm pins</p>  <p>Exposed (naked) 0.9 mm pins/breaking needles</p>
	 <p>Article No: 81832</p> <p>Bipolar plug fitting bipolar terminals of PACE® Model 203</p> <p>Covered alligator clips allow versatile connection</p> <p>Packaging Unit: 10 Pieces</p>		
	Reusable Extension Cable StimConnect™		
	 <p>Article No: 82202BL (blue) / 82202WS (white)</p> <p>Bipolar plug fitting bipolar terminals of PACE® Model 203</p> <p>Connects exposed (naked) pins with diameter between 0 to 2.0 mm</p> <p>Packaging Unit: 5 Pieces</p>		 <p>Adapters with exposed (naked) 2 mm pins</p>  <p>Exposed (naked) 0.9 mm pins/breaking needles</p>

OSYPKA
MEDICAL

Products and options may not be available or may vary by region and country. Please contact mail@osypkamed.com for availability in your region and country, for more information and for other StimConnect® extension cable variants.









StimConnect™

for PACE® Model 300 with Unipolar Terminals

Extension Cables for Surgical Pacing Applications

PACE® Model 300 is primarily used for temporary surgical cardiac pacing applications. Surgical wires (temporary myocardial electrodes or heart wires) for temporary pacing are either equipped with 2 mm exposed (naked) plug pins or 0.9 mm pins/ needles. Alligator clips facilitate extraordinary temporary pacing applications.

Disposable cables are for single use, reusable extension cables can be sterilized 25 times by ethylene oxide or steam. A punch card allows the identification of the sterilization cycles.

Pacemaker	Disposable Extension Cable StimConnect™		Surgical Pacing Electrode
	Connection Pacemaker- Side	Connection Patient-Side	
	 <p>Article No: 81987BL (blue) / 81987 WS (white)</p> <p>Plugs with touch protected 2 mm pins fitting unipolar terminals of PACE® Model 300</p> <p>Connects exposed (naked) pins with diameter between 0.9 to 2.0 mm</p> <p>Packaging Unit: 5 Pieces</p>		 <p>Adapters with exposed (naked) 2 mm pins</p>  <p>Exposed (naked) 0.9 mm pins/ breaking needles</p>
	 <p>Article No: 81830</p> <p>Plugs with exposed 2 mm pins fitting unipolar terminals of PACE® Model 300</p> <p>Covered alligator clips allow versatile connection</p> <p>Packaging Unit: 10 Pieces</p>		
	 <p>Article No: 81828BL (blue) / 81828 WS (white)</p> <p>Plugs with exposed 2 mm pins fitting unipolar terminals of PACE® Model 300</p> <p>Connects exposed (naked) pins with diameter between 0 to 2.0 mm</p> <p>Packaging Unit: 5 Pieces</p>		 <p>Adapters with exposed (naked) 2 mm pins</p>  <p>Exposed (naked) 0.9 mm pins/ breaking needles</p>

PACE® Model 300 with unipolar terminals accepting pins of 0.9 to 2.0 mm

(order number: P/N 2005)



Products and options may not be available or may vary by region and country. Please contact mail@osypkamed.com for availability in your region and country, for more information and for other StimConnect® extension cable variants.