

PACE® Model 101

SINGLE CHAMBER (SSI)
TEMPORARY PACEMAKER



Now available with terminals for bipolar connectors and touch-protected channels for 2 mm pins of temporary pacemakers.

PACE® Model 101 Highlights

- Easy to configure and operate
- Constant voltage output for reliable cardiac capture (similar to permanent pacemakers)
- Small and lightweight design
- Lifetime service

Two terminal options

- P/N 2001: Clamping terminals accepting pins of 0.9 to 2.0 mm diameter
- P/N 2004: Bipolar terminal and 2 unipolar terminals for touch-protected ("shrouded") 2 mm pins



Specifications	PACE® Model 101	
Modes	AAI, A00, VVI, V00	
Basic Pacing Rates	30 – 180 ppm	
Rapid Atrial Pacing Rates	Basic Rate x2 (60 – 360 ppm) Basic Rate x4 (120 – 720 ppm)	
Output Amplitude	0.3 – 12 V	
Pulse Width	0.75 ms	
Sensitivity Threshold	1.0 – 20 mV, asynchronous	
Refractory Period	250 ms	
Dimensions	P/N 2001: 6.0 cm x 14.2 cm x 2.2 cm (2.36" x 5.6" x 0.87")	P/N 2004: 6.0 cm x 11.5 cm x 2.2 cm (2.36" x 4.53" x 0.87")
Weight incl. Battery	170 g (6.0 ounces)	
Battery Type	9V Type 6LP3146 Alkaline	
Battery Life	Alkaline: Up to 38 days (72 ppm, 8.0 V)	

Products and options may not be available in every region or country. Please contact mail@osypkamed.com for availability in your region and country and for further information.

Osypka Medical GmbH

Albert-Einstein-Strasse 3
12489 Berlin, Germany
Phone: +49 (30) 6392 8300
Fax: +49 (30) 6392 8301
E-Mail: mail@osypkamed.com
www.osypkamed.com

United States of America:
Osypka Medical, Inc.
dba. Cardiotronic

La Jolla, CA 92037, USA
Phone: +1 (858) 454 0600
Fax: +1 (858) 454 0640
E-Mail: mail@cardiotronic.net
www.cardiotronic.net

PACE and the logos are
trademarks of Osypka Medical.

